


Narrow Sofa Table

Difficulty

Advanced

This narrow sofa table is a stylish piece for behind the sofa or use as a console table in the hall. Easily adjust the dimensions for height or length to fit perfectly in your space. Inspired by a console table as seen on Houzz. If you don't have tools to cut curves, substitute straight boards.



Tools

Kreg Tools

Wood
Project [Wood Project Clamp - 6"](#)
Clamp -
6

Kreg®
Pocket-
Hole Jig [Kreg® Pocket-Hole Jig 720](#)
720

Other Tools

Miter Saw

Tape Measure

Band Saw

Drill (cordless)

Nail Gun

Sander

Materials

Wood Products


- 1** Board , 2x12 , 96"
- 1** Board , 4x4 , 96"
- 1** Board , 2x4 , 96"
- 2** Board , 1x3 , 96"

Hardware & Supplies

- 20** 2 1/2" Pocket Screws
- 18** 1 1/4" Pocket Screws
- 25** 1 1/4" Brad Nails
- 1** Carrington Stain
- 1** Wood Glue
- 3** Sandpaper
- 1** Top Coat/Polyurethane

Cut List & Parts

- 1 Top , 1 1/2" X 11 1/4" X 64"
- 2 Skirt , 3/4" X 2 1/2" X 62"
- 2 Skirt , 3/4" X 2 1/2" X 7 3/4"
- 2 Leg , 3 1/2" X 3 1/2" X 26"
- 2 Feet , 3 1/2" X 3 1/2" X 14 1/2"
- 1 Rail , 1 1/2" X 3 1/2" X 53 1/2"
- 2 Arch , 1 1/2" Thick See Pattern In Extras
- 4 Molding , 1 1/2" X 3 1/2" See Pattern In Extras




Directions

1**Make and Assemble Legs**

Cut the legs and feet from a 4x4. Trace and cut out the pattern for the feet with a band saw. Drill 1 1/2" pocket holes in the front and back of the legs (top and bottom). Mark the center of the legs and feet and secure together with wood glue and 2 1/2" pocket hole screws.


Note: Instead of cutting curves on the feet, consider making a 45 deg cut on the ends for simple style. If making the table to go along a wall, shorten the feet to 11 1/4" (from 14 1/2").



2

Attach Rail

Cut the rail from a 2x4. Drill 1 1/2" pocket holes in each end (under side). Mark the centers of the rail ends and feet. Secure the rail to the feet with wood glue and 2 1/2" pocket hole screws.




3

Assemble Skirt


Cut the skirt pieces from the 1x3's. Drill 3/4" pocket holes in each end of the 7 3/4" skirt pieces. Also drill 3/4" pocket holes in the skirt pieces to attach to the top later. Assemble the skirt together using wood glue and 1 1/4" pocket holes.

Note: The short pocket hole driver is useful while assembling the skirt. If necessary, drill through the backside of the skirt into the 7 3/4" pieces.




4**Attach Skirt to Top**

Cut the top piece from the 2x12. Center the skirt onto the underside of the top piece. Use wood glue and 1 1/4" pocket hole screws to secure the skirt to the top.



5**Attach Legs to the Top**


Center the legs onto the top piece. Use wood glue and 2 1/2" pocket hole screws to secure the legs to the table top.



6

Cut and Attach Arch

Trace 2 arches onto the remaining 2x12. Use a band saw, scroll saw or jig saw to cut out the arches. Sand the arches smooth. Center an arch to a leg and top, attach with wood glue and 1 1/4" brad nails. Repeat for the second arch.



7

Add Molding

Trace 4 molding patterns onto some of the remaining 4x4. Cut out the molding pieces with a band saw. Sand the pieces smooth. Attach to the front and back of the leg pieces with wood glue and 1 1/4" brad nails. The molding pieces will cover up the leg pocket holes. Alternately you can use store bought molding.

Sand the narrow sofa table smooth, ending with 120-150 grit sandpaper. Stain the table as desired and protect with top coat/polyurethane.

